ErgoRack

PRIME DESIGN

A Safe Fleet Brand

For Nissan NV Cargo







Easy to use

Deploys with only 2 fingers.



Improve productivity

Deploy or stow in less than 20 seconds.



Enhance Safety

Eliminates slip and fall hazards from climbing on bumper or tire.



No Drill Installation

Maintain vehicle warranty and resale value with no holes to drill.



ErgoRack

For Nissan NV Cargo



A Safe Fleet Brand







HBB-NV

Base Rack

HRR-NV

Dual Rotation

HRR3-NV

Dual Rotation with 3rd crossbar

Models	Vehicle Wheelbase	Vehicle Height	Street side Feature	Curb side Feature	Weight
HBB-NV	146 IN	84 IN (Standard) or 105 IN (High)	End Stop	End Stop	33 lbs
HBR-E-NV HRB-E-NV	146 IN	84 IN (Standard) or 105 IN (High)	End Stop	Rotation	88 lbs
HRR-E-NV	146 IN	84 IN (Standard) or 105 IN (High)	Rotation	Rotation	143 lbs
HRR3-E-NV*	146 IN	84 IN (Standard) or 105 IN (High)	Rotation	Rotation	154 lbs

^{*}Three crossbar rack

Notes

Crossbar spacing and the vehicle's wheelbase length will dictate the ladders that can be carried. Crossbars can be spaced at six, seven, or eight feet.

A 3rd crossbar can be spaced four, five, six, or seven feet.

If carrying a long extension ladder and a short step ladder, a three crossbar rack is suggested. Contact Prime Design customer service for application specific questions.

Check the vehicle manufacturer's recommendation for roof capacity weight limits.

A wide range of accessories are available including conduit carriers, light holders, and more.

Van Crossbar Spacing and Ladder Size Guide

Step Ladder Size	Extension Ladder Size
6 – 8 ft.	16 – 20 ft.
8 – 10 ft.	16 – 24 ft.
8 – 12 ft.†	16 – 28 ft.
10 – 12 ft.†	20 – 32 ft.
10 – 12 ft.†	20 – 36 ft.
	6 – 8 ft. 8 – 10 ft. 8 – 12 ft.† 10 – 12 ft.†

^{†12} ft. step ladders may require an extended upper add-on component.

NISSAN PREFERRED SHIP-THRU SUPPLIER

